

UNIVERSAL PULLEY

with rope and rope break



WITH ROPE BRAKE

ARTICLE-NO.	10814	10869
Description	Schöco 22B	Schöco 30B
Lifting height (m)	2,5	2,5
Transmission ratio	6:1	8:1
Breaking Load Limit (kg)	800	1000
Working Load Limit (kg)	220	300
Rope length (m)	18	22
Total height (mm)	300	300
Weight (kg)	0,80	1,00

PRODUCT INFORMATION

- Easy handling: fast lifting, pulling and tensioning
- High stability: sheet steel housing with safety hooks
- High-quality: rollers made of polyamide
- Polypropylene rope with 6 mm diameter
- High safety: breaking load check through independent testing institution in Remscheid, Germany
- Individual lifting height: upon request, a 16-fold woven multi-filament yarn without swirl for lifting heights up to 7 meters can be supplied

USAGE INFORMATION

- Check all parts for wear mark to ensure perfect functioning before using
- Only use the pulley for the load capacity and rope diameter specified!
- When using:
 - do not stand or walk under the pulley! Danger of life!
 - use gloves to prevent hand injuries
- **WARNING! When using do not exceed load capacity!**
- **The special knot of the rope on the upper, fixed bracket is self-retaining and therefore not to be opened under any circumstances!**



INSTRUCTIONS



www.schoerken.com/en/downloads-en/#Universal-pulley-rope-and-rope-break